

Application Scenarios



Specifications

|                        |   |                        |
|------------------------|---|------------------------|
| Model                  | P50 Pro   | P50                    |
| Memory                 | RAM (2 GB), ROM (32 GB)   | RAM (1 GB), ROM (8 GB) |
| Weight                 | 208g  | 190g                   |
| NFC                    | Available   | /                      |
| Camera                 | 8 MP, 1080p@30fps   | /                      |
| Sensor                 | Optical distance sensor, Gravity sensor   | /                      |
| Numeric Keypad         | Available   | /                      |
| Frequency Range        | EU version<br>GSM: 850/900/1800/1900<br>WCDMA: B1/B3/B5/B8<br>LTE TDD: B34/B38/B39/B40/B41<br>LTE FDD: B1/B3/B5/B7/B8/B18/B19/B20/B26/B28<br>US version<br>GSM: 850/900/1800/1900<br>WCDMA: B2/B4/B5<br>LTE TDD: B38/B41<br>LTE FDD: B2/B3/B4/B5/B7/B12/B13/B17/B26/B28 |                        |
| Core Frequency         | 2.0GHz  |                        |
| Operating System       | Android 12  |                        |
| Dimensions (H x W x D) | 131 mm x 61 mm x 23.5 mm  |                        |
| Screen                 | 2.4-inch color LCD screen, 320 x 240 pixels   |                        |
| Location               | GPS/BDS/GLONASS/Galileo/AGPS<br>BDS only (optional)   |                        |
| WLAN                   | WLAN 5 802.11 (2.4G/5G) ac/a/b/g/n  |                        |
| Speaker Power          | 2 W (rated), 3 W (max.)   |                        |
| Battery                | 4,000 mAh   |                        |
| Interface              | 9-pin audio connector, USB Type-C   |                        |
| Card Slot              | Nano SIM card slot x 1, TF card slot x 1  |                        |
| Operating Temperature  | -20°C to + 60°C   |                        |
| Storage Temperature    | -30°C to + 70°C   |                        |
| ESD                    | IEC 61000-4-2, (ESD) ±12 kV (Air), ±8 kV (Contact)  |                        |
| IP Rating              | IP68  |                        |
| Drop Resistance        | 1.5 m   |                        |
| Certificate            | CE  |                        |
| Man Down               | Support <sup>1</sup>  |                        |
| Lone Worker            | Support <sup>2</sup>  |                        |
| MIL-STD 810H           | Support   |                        |

<sup>1</sup>P50 Pro Only  
<sup>1&2</sup> Available with the Hytera Hytalk Platform.

**Hytera Communications Corporation Limited**  
Stock Code: 002583.SZ  
Address: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, P.R.C  
Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057  
Https://www.hytera.com marketing@hytera.com

Accessories



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd.  
© 2024 Hytera Communications Corp., Ltd. All Rights Reserved.



P5 Series PoC Radio

Where Reliability Meets Simplicity





## Reliability

### Overview

The Hytera P5 Series is a powerful PoC radio that leverages push-to-talk (PTT) over cellular networks, providing nationwide coverage and enhanced communication efficiency. By combining exceptional PTT performance with advanced data capabilities, it empowers professionals in security, logistics, transportation, and urban management to communicate effectively and collaborate seamlessly.

### Ruggedized Connector & Port

Feature a 9-pin audio connector with a screw-in design to securely attach the earpiece to the radio. The waterproof Type-C charging port, crafted from high-strength alloy, ensures durability for long-term use.

### Always Connected

Stay connected with the P5 Series, even in areas with weak signals. Its professional dual antenna design delivers excellent signal performance, ensuring seamless communication, for instance in B5 band with a TRP of 18.5 dBm and a TIS of -93.5 dBm.

### Power for Longer Shifts

Equipped with a low-power, high-performance chip and a 4,000 mAh battery, the P5 Series offers up to 30 hours\* of operation.

**\*Operating on a 10-10-80 duty cycle**



### Superior Audio Quality

#### Ultra Loudness

Equipped with a 3W built-in speaker and a professional cavity design, it delivers a loudness of up to 103 dB at 30 cm, ensuring clarity in noisy environments.

#### Crystal Clarity

Advanced noise cancellation filters out surrounding sounds for clear communication, while howling suppression eliminates feedback when radios are close together, ensuring messages are transmitted without interruption.

#### High Fidelity

Utilizing wideband audio processing technology with a 16 kHz sampling rate and a frequency range of 20 Hz to 8 kHz, it reproduces sound naturally for enhanced clarity and understanding.

## Simplicity

### Work Jointly in Seconds

With Quick Group\*, the P5 Series enables you to create or join a group instantly, saving time and enhancing teamwork.

**\*Optional**

### Clone Your Radio, Simply and Swiftly

With Radio Clone\*, the P5 Series allows for quick configuration cloning from one radio to multiple radios via WiFi.

**\*Optional**



### Interact with Info Intuitively

The large 2.4-inch color screen features a full-view display\* with an intuitive UI, allowing for flexible shoulder and waist wearing. This design enables quick access to key information at a glance.

**\*P50 Pro only**

### Rotate. Hear. Well done!

The group switch knob enables quick group switching. Paired with Voice Notification\*, the P5 Series informs you of the group you've switched to, helping you stay focused on your tasks.

**\*Coming soon**

All data is from lab testing; actual results may vary based on environmental conditions.

